

CORRECTED VERSION

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number  
**WO 2005/087685 A1**

(51) International Patent Classification<sup>7</sup>: **C04B 24/26**,  
24/32, C08F 220/18, 290/06

(21) International Application Number:  
PCT/JP2005/005070

(22) International Filing Date: 15 March 2005 (15.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2004-074017 16 March 2004 (16.03.2004) JP

(71) Applicant (for all designated States except US): **NIPPON SHOKUBAI CO., LTD.** [JP/JP]; 1-1, Koraihashi 4-chome, Chuo-ku, Osaka-shi, Osaka, 5410043 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **YAMAMOTO, Takashi** [JP/JP]; 9-10-405, Takashirocho, Suita-shi, Osaka, 5640024 (JP). **MASANAGA, Mari** [JP/JP]; 31-15, Maruyamacho, Suita-shi, Osaka, 5640061 (JP). **KAWA-BATA, Hiroshi** [JP/JP]; 4-52-C307, Nakanoshimacho, Suita-shi, Osaka, 5640035 (JP).

(74) Agents: **HATTA, Mikio** et al.; Dia Palace Nibancho, 11-9, Nibancho, Chiyoda-ku, Tokyo, 1020084 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(48) Date of publication of this corrected version:  
24 November 2005

(15) Information about Correction:  
see PCT Gazette No. 47/2005 of 24 November 2005, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DRYING SHRINKAGE-REDUCING AGENT



stands for a hydrocarbon group of 4 - 30 carbon atoms, and exhibiting surface tension in the range of 25 - 50 mN/m in a solution containing 0.2 mass% of the polymer in a cement supernatant is provided. The drying shrinkage-reducing agent manifests no dispersability in an amount capable of attaining necessary drying shrinking-reducing properties and, when used in combination with a dispersing agent, acquires ability to adjust the dispersability and the drying shrinkage-reducing properties fit for the purpose.

(57) Abstract: A drying shrinkage-reducing agent which comprises a polymer containing as an essential component at least one structural unit (I) represented by the following formula (1): [Chemical 1] wherein R<sup>1</sup>, R<sup>2</sup>, and R<sup>3</sup> independently stand for a hydrogen atom, a methyl group, or a -(CH<sub>2</sub>)<sub>p</sub>COOX group, wherein X stands for a hydrogen atom, a monovalent metal, a divalent metal, an ammonium group, an organic amine group, or a hydrocarbon group, and p is an integer of 0 - 2; and R<sup>4</sup>



WO 2005/087685 A1